GSM Scout protect LTE

Counteracting to burglary and thefts - Easy monitoring and telecontrolling by SMS from your cell phone.



ConiuGo GmbH Gesellschaft für Telekommunikation

Order no.: 700100212L

Applications

Monitoring of:

- Home
- Cottage
- Boats, caravans, etc.

Teleswitching of:

- Light
- Alarm siren
- Air conditioner



General information

The GSM Scout protect LTE can be used for monitoring homes and cottages. Because of ist small dimensions, it is easy to hide at any place. With its internal motion sensor, unallowed entering of parcels is reported up to 4 customized numbers. Because of direct, quiet alarming, burglary can be detected directly, which makes prosecution quite easy. The triggering of electrical devices by SMS is also possible, because of internal switching relais.

For protecting the circurities of burning damages, using a R/C protection combination is recommended.

Technical specific features

- Easy installation
- Easy customization with SIM card
- Easy to hide, because of small dimensions
- Different housing colours

Functional extension e-mail

Alarm text via e-mail (in addition to SMS)

Conditions

For using the GSM Scout protect LTE is required: GSM antenna, 4,5 VDC, SIM card (prepaid or contract), sensors

Technichal data

Temperature range

Interfaces

Mobile phone network Usable with all generall mobile providers Scope of supply GSM Scout protect

- 20 °C until + 60 °C working temperature

1 register circles for "break ins"

Battery package Liion 3,7 V / 1035 mAh

Customization SIM card customization by cell phone Manual

Miniature screwdriver for brackets

Dimensions / weight $123 \times 70 \times 25 \text{ mm}$ (W x L x H) / 104 g Screws of the housing

Functional extension Alarm message and arming via e-mail and/or SMS,

configuration with USB cable on the PC, server setup

2 x relaiy contacts and usage for 1 year

Order no. 701100921 (used for 1 year)

Power supply 11 - 35 V DC, 60 mA,

Standby: 0,06 A, Optional accessoires Power supply 230 V AC / 12 V DC 305307214
Battery charging: 0,66 A, Glass attached antenna (indoor), 300303304S

SMS sending: 0,15 A requirement 1,5 m cable (SMA)

Round antenna PUK (outdoor), 300303310S

Motion sensor Range: 5 m / 100° horizontal, 82° vertical 3 m cable (SMA)

Fon: +49 (0)3303 - 409 639 Fax: +49 (0)3303 - 409 691

3 m cable (SMA)
R/C protection 700100618

web: www.coniugo.com

e-mail: hit@coniugo.com

Different sensors on request

06/2014

Order no.: