

EasyGuard II

Supervising and telemetry simple by SMS from your mobile phone

ConiuGo

ConiuGo GmbH
Gesellschaft für Telekommunikation

Ordernr.: 700100107S (0-1 V)
700100108S (0-20 mA)

Applications

- Security and alarm management
- supervising of houses
- supervising of huts, boats, yachts, caravar
- facility management
- smoke and fire detection
- many other applications



General information

The EasyGuard II is a compact event messaging and telemetry module for the GSM networks. Several events will be registered like analogue measurements (e.g. temperature, air dump, etc.), time frames as well as incoming SMS. Actions after such an event could be the sending of SMS to up to 4 numbers and the switching of integrated relays.

Technical specific features

- simple connection by screw contacts
- no special software necessary
- parallel and cascade messaging up to 4 numbers
- analogue Inputs with messaging function

Conditions

To use the Easy Guard II, you need the following equipment: Power supply (stabilised), activated SIM card (Prepaid or time contract), Sensors and actors as needed

Technical data

GSM networks GSM 850 + 900 + 1800 + 1900 MHz networks

Configuration Enter of application settings in masks at the PC,
Transfer of settings from the PC to the Module

**Physical Dimensions/
weight** 130 x 115 x 45 mm (L x H x W) / 178g

Temperature range - 30 °C bis + 60 °C work temperatur

Interfaces 4 digital inputs for reed contacts,
4 analogous inputs for temperature measurements,
2 digital outputs for telemetry
(relay contacts 24 V, 1 A resilient
D-SUB 9pin (emale), RS232
SMA (female) 50 Ohm for antenna

Energy supply 11-35 V DC

Scope of supply EasyGuard II
Manual

Optionale accessories Mains Power Supply 12 V DC
Glass Attached Antenna (Indoor use),
1,5 m cable (SMA)
Round Antenna PUK (Outdoor use),
3 m cable (SMA)
Various sensors on request

Bestell-Nr.
305307214
300303304S

300303310S